





# **INDEX**

Product Line	Page
Fast Recovery Heat Shrink Kits	1
Deluxe Heavy Duty Heat Shrink Kits	1
Heavy Duty Heat Shrink Kits	2
Heat Shrink Tubes	3
Stakon Connectors	3
Electrical Tape	4
"All Weather" Pipe Wrap Tape	4
Cable Ties	4
Submersible Torque Arrestors	5
Spider Torque Arrestors	6
Cable Guards	6
Drop Pipe Couplings	6
Rope	7
Rope Hanger	7
Mechanical Shaft Seals	8
Circulator Coupling	8
Nut Driver	8
Pipe Cutters	9
Contractor Bin	9
Tape Measures	10

Toll Free: 1-800-561-3164 boshart.com



### **FAST RECOVERY HEAT SHRINK KITS**

Boshart's fast recovery heat shrink kits are made of adhesive lined cross-linked polyolefin heat shrinkable tubing that is designed for applications up to 600 volts. The good abrasion resistance characteristics of this tubing provide excellent mechanical protection. When heated above 120°C (250°F) there is a 4:1 shrink ratio. Upon cooling the adhesive solidifies, forming a permanent, non-drying flexible and waterproof barrier. Black tubing is flame retardant, clear tubing is not flame



• RoHS Certified directive 2002/95/EC <0.1% Pb

	Part No.	Number of Stakons	Number of Shrink Tubes	Tube Length	Wire Size AWG	Wall Thickness List Price Effe		List Price - A
						LIST PITCE ETTE	ctive: Octob	er 15, 2021
	Black, Expa	nded ID: 0.45", Recov	vered ID: 0.10"					
	HSKB-2	2 (#14 - #10)	2	3"	#14 to #10	0.043"	50	\$ 2.12
	HSKB-3	3 (#14 - #10)	3	3"	#14 to #10	0.043"	50	\$ 2.98
	HSKB-3-4	4 (#14 - #10)	3	3"	#14 to #10	0.043"	50	\$ 3.33
	HSKB-4	4 (#14 - #10)	4	3"	#14 to #10	0.043"	50	\$ 3.83
SN1 =-	Clear, Expa	nded ID: 0.45", Recov	ered ID: 0.10"					
CAN ==	HSKC-2	2 (#14 - #10)	2	3"	#14 to #10	0.043"	50	\$ 2.17
	HSKC-3	3 (#14 - #10)	3	3"	#14 to #10	0.043"	50	\$ 3.06
2000	HSKC-3-4	4 (#14 - #10)	3	3"	#14 to #10	0.043"	50	\$ 3.40
	HSKC-4	4 (#14 - #10)	4	3"	#14 to #10	0.043"	50	\$ 3.93
	HSKC-12	12 (#14 - #10)	12	3"	#14 to #10	0.043"	50	\$ 10.91

### **DELUXE HEAVY DUTY HEAT SHRINK KITS**

Boshart's deluxe heavy duty heat shrink kit series have the same heat shrink tubes as the heavy duty heat shrink kits. They have extra long stakons (butt conn) for double crimping. • RoHS Certified directive 2002/95/EC <0.1% Pb



Number of Tube Wire Size Part No. Number of Wall Quantity List Stakons **Shrink Tubes** Length AWG Thickness L1 L2 Price - A List Price Effective: October 15, 2021 Black, Expanded ID: 0.75", Recovered ID: 0.24" HS4-4XLS 3 (#4) & 1 (#6) 4.80" #4 0.090" 10 \$ 44.73 Clear, Expanded ID: 0.75", Recovered ID: 0.22" HSC4-4XLS 3 (#4) & 1 (#6) 4.80" #4 0.080" 10 \$ 43.34 Black, Expanded ID: 0.51", Recovered ID: 0.16" HS6-3XLS 2 (#6) & 1 (#8) #6 0.090" 10 \$ 26.96 HS6-4XLS 3 (#6) & 1 (#8) 4' 0.090" 4 #6 10 \$ 35.88 Clear, Expanded ID: 0.75", Recovered ID: 0.22" HSC6-4XLS 3 (#6) & 1 (#8) 4" #6 0.080" 10 \$ 35.91 Black, Expanded ID: 0.51", Recovered ID: 0.16" HS8-3XLS 2 (#8) & 1 (#14 - #10) 3 4" #8 0.090" 10 \$ 19.48 HS8-4XLS 3 (#8) & 1 (#14 - #10) 4 4" #8 10 0.090" \$ 27.31 Clear, Expanded ID: 0.75", Recovered ID: 0.22" HSC8-4XLS 3 (#8) & 1 (#14 - #10) 4 4" #8 0.080" \$ 26.87 10



## **HEAVY DUTY HEAT SHRINK KITS**

Boshart's heavy duty heat shrink kit series are make of flexible cross-linked polyolefin heat shrinkable tubing. This tubing is suitable for applications up to 600 volts providing excellent waterproof insulating and environmental sealing protection for splices, connections and jacket repairs. The high impact and abrasion resistance of this heavy wall tubing provides the highest level of mechanical durability. When heated above 120°C (250°F) there is a 3:1 shrink ratio.
• RoHS Certified directive 2002/95/EC <0.1% Pb



Part No.	Number of Stakons	Number of Shrink Tubes	Tube Length	Wire Size AWG	Wall Thickness List Price Effe		Price - A
Black, Expa	nded ID: 0.75", Recover	ed ID: 0.24"				'	
HS4-4	3 (#4) & 1 (#6)	4	4.80"	#4	0.090"	10	\$ 23.79
Clear, Expa	nded ID: 0.75", Recovere	ed ID: 0.22"					
HSC4-4	3 (#4) & 1 (#6)	4	4.80"	#4	0.080"	10	\$ 21.53
Black, Expa	nded ID: 0.51", Recover	ed ID: 0.16"					
HS6-3	2 (#6) & 1 (#8)	3	4"	#6	0.090"	10	\$ 12.85
HS6-4	3 (#6) & 1 (#8)	4	4"	#6	0.090"	10	\$ 17.05
Clear, Expa	nded ID: 0.75", Recover	ed ID: 0.22"					
HSC6-4	3 (#6) & 1 (#8)	4	4"	#6	0.080"	10	\$ 17.06
Black, Expa	nded ID: 0.51", Recover	ed ID: 0.16"					
HS8-3	2 (#8) & 1 (#14 - #10)	3	4"	#8	0.090"	10	\$ 10.52
HS8-4	3 (#8) & 1 (#14 - #10)	4	4"	#8	0.090"	40	\$ 13.85
Clear, Expa	nded ID: 0.75", Recover	ed ID: 0.22"					
HSC8-4	3 (#8) & 1 (#14 - #10)	4	4"	#8	0.080"	10	\$ 14.06
Black, Expa	nded ID: 0.40", Recover	ed ID: 0.15"					
HS-2	2 (#14 - #10)	2	3"	#14 to #10	0.080"	50	\$ 2.46
HS-3	3 (#14 - #10)	3	3"	#14 to #10	0.080"	50	\$ 3.47
HS-3-4	4 (#14 - #10)	3	3"	#14 to #10	0.080"	50	\$ 3.82
HS-4	4 (#14 - #10)	4	3"	#14 to #10	0.080"	50	\$ 4.40
	nded ID: 0.40", Recovere						
HSC-2	2 (#14 - #10)	2	3"	#14 to #10	0.080"	50	\$ 2.46
HSC-3	3 (#14 - #10)	3	3"	#14 to #10	0.080"	50	\$ 3.47
HSC-4	4 (#14 - #10)	3	3"	#14 to #10	0.080"	50	\$ 3.82

HSC-4

4 (#14 - #10)

\$ 4.40

0.080"

#14 to #10

50



# **HEAT SHRINK TUBES**

These heat shrink tubes are sold in bulk rather than part of a kit.

• RoHS Certified directive 2002/95/EC <0.1% Pb



Part No.	Tube Length	Expanded ID	Recovered ID	Wire Size AWG	Wall Thickness	Quantity L1 L2	List Price - A
					List Price Effe	ctive: Octob	er 15, 2021
Black • List price is per	piece						
HST-HS-3-BK	3"	0.40"	0.15"	#14 to #10	0.080"	25	\$ 1.03
HST-HSK-3-BK	3"	0.45"	0.10"	#14 to #10	0.043"	25	\$ 0.83
Clear							
· List price is per	piece						
HST-HS-3-CL	3"	0.40"	0.15"	#14 to #10	0.080"	25	\$ 1.03
Black • List price is per	inch						
HST400-48-BK	48"	0.40"	0.15"	#14 to #10	0.080"	48	\$ 0.51
HST500-48-BK	48"	0.51"	0.16"	#8 to #6	0.090"	48	\$ 0.62
HST750-48-BK	48"	0.75"	0.24"	#6 to #2	0.090"	48	\$ 0.65
HST1100-48-BK	48"	1.10"	0.35"	#1 to #3/0	0.120"	48	\$ 1.11
	48"	1.50"	0.47"	#2/0 to #350	0.160"	48	\$ 1.33
HST1500-48-BK	40	1.30	0.47	#2/0 (0 #330	0.100	70	Ψ 1.55
Clear	-	1.50	0.47	#2/0 (0 #330	0.100	40	Ψ 1.33
	-	0.40"	0.47	#14 to #10	0.080"	48	\$ 0.51

# **STAKON CONNECTORS**

These stakon connectors are sold in bulk rather than part of a kit.



Part No. Wire Size AWG Quantity List
L1 L2 Price - A

List Price Effective: October 15, 2021







Deluxe				
SC-2XLS	#2	4	100	\$ 12.18
SC-4XLS	#4	4	200	\$ 10.41
SC-6XLS	#6	10	200	\$ 7.97
SC-8XLS	#8	10	200	\$ 6.72

boshart.com



### **ELECTRICAL TAPE**

Boshart's electrical tapes are available for a wide range of applications.

- CSA Standard C22.2 No. 0 & 197 Certified
- UL Standard 570 Certified
- RoHS Certified directive 2002/95/EC <0.1% Pb



Thickness Part No. Size Length Quantity List 11 L2 Price - A



10



#### **Electrical Tape**

ETCWNL

Temperature Range: 14°F to 176°F (-10°C to 80°C),

This vinyl tape is a general all purpose tape.

60' 0.007" (7 mils) 10 200 \$ 2.64



### **Cold & Sunlight Electrical Tape**

Temperature Range: 0°F to 176°F (-18°C to 80°C),

This vinyl tape is for use as electrical insulation on joints & splices in wires and cables, protective outer jacket, harness wrapping and protective conduits. It is for low temperature applications and resists abrasions, alkalis, acids, oil, solvents, corrosive chemicals, ultraviolet rays & moisture. Retardant to flames. It has a plastic backing & aggressive rubber-resin adhesive. This cold & sunlight electrical tape offers moisture tight electrical & amp; mechanical protection.

0.008" (8 mils)



### **Self Bonding Electrical Tape**

Temperature Range: 14°F to 176°F (-10°C to 80°C),

This tape is a self fusing rubber electrical insulating tape. It is designed for low voltage electrical insulating & moisture sealing applications. Compatible with solid dielectric cable insulation. It is recommended that this tape should be over wrapped for mechanical protection with two half lapped layers of electrical tape or cotton friction tape.

ETSBR 0.03" (30 mils)

### "ALL WEATHER" PIPE WRAP TAPE

60'

Boshart's all weather pipe wrap tape can be used on all types of pipe and fittings including steel, galvanized, electrical conduit, cast & ductile iron. It has excellent insulating capacities and superior abrasion resistance. This tape reduces corrosion problems caused by salts, salt water, solid acids, minerals, alkalis, common chemicals, vapors and protects against fungus and bacteria. It remains pliable in a wide range of temperature and working environments, resists the effects of outdoor weathering and sunlight exposure.



- IAPMO UPC Standard D100 Certified
- RoHS Certified directive 2002/95/EC <0.1% Pb

Part No. Length **Thickness** Quantity List L2 Price - A List Price Effective: April 27, 2020



Temperature Range: 14°F to 140°F (-10°C to 60°C) PW2-10NL 2' 100 0.01" (10 mils) 24 \$ 13.16

### **CABLE TIES**

Boshart's cable ties are very versatile and can be used in a variety of applications. They are NEMA Type 2, 21.

- ANSI/UL 94 Mtl Flame Rating V-2
- ANSI/UL Standard 62275 Certified

Part No. Color Length



L1 L2 Price - A

Quantity List

List Price Effective: May 14, 2021



Standard Nylon 6/6, Temperature Range: -40°F to 185°F (-40°C to 85°C),

- · Carbon is added to make these UV resistant
- Suitable for indoor and outdoor use

_						
	CTW018-04	4.00"	Black	100		\$ 0.03
	CTW030-05.6	5.60"	Black	100		\$ 0.07
	CTW040-08.5	8.50"	Black	100		\$ 0.09
	CTW040-11.5	11.50"	Black	100		\$ 0.15
	CTW040-14.5	14.50"	Black	100	5000	\$ 0.19

Contact your sales rep for any further information

Toll Free: 1-800-561-3164 boshart.com



## **CABLE TIES**

Part No. Length Color Quantity List L1 L2 Price - A

List Price Effective: May 14, 2021



Standard Nylon 6/6, Temperature Range: -40°F to 185°F (-40°C to 85°C),

- Not UV resistant
- · Suitable for mainly indoor use

CT018-04	4.00"	Clear	100	\$	0.03
CT030-05.6	5.60"	Clear	100	\$	0.07
CT040-08.5	8.50"	Clear	100	\$	0.09
CT040-11.5	11.50"	Clear	100	\$	0.14
CT040-14.5	14.50"	Clear	100	5000 \$	0.18

Heavy Duty Nylon 6/6, Temperature Range: -40°F to 185°F (-40°C to 85°C),

- · Carbon is added to make these UV resistant
- Suitable for indoor and outdoor use

CTW120-14.2	14.20"	Black	100	2000	\$ 0.36
CTW120-24.2	24.20"	Black	50	500	\$ 0.69
CTW175-36	36.00"	Black	50	500	\$ 0.82
CTW175-41	41.00"	Black	50	500	\$ 1.66

## SUBMERSIBLE TORQUE ARRESTORS

Color

Boshart's submersible torque arrestors protect submersible pumps from starting torque damage. They are field adjustable to hold the pump centered in the well and fit snug in all well casings from 4" to 8" I.D. To install securely fasten to 1", 1-1/4" or 2" drop pipe with stainless steel clamps that are provided. There are infinite adjustments enabling the installer to obtain a proper fit.

**Drop Pipe Size** 



Quantity List

**Well Casing Size** 



• NSF/ANSI 372 Certified

Part No.

				L1	L2	Price - A
				List Price Effective:	List Price Effective: October	
Standard Therr	no Plastic Elastome	r (TPE)				
TA-48-BLK	1" & 1-1/4"	Black	4" to 8"	10	560	\$ 25.26
TA-48-GREEN	1" & 1-1/4"	Green	4" to 8"	10	560	\$ 26.56
Standard PVC						
TA-48-PVC	1" & 1-1/4"	Black	4" to 8"	10	560	\$ 20.98
Deluxe Thermo	Plastic Elastomer (	TPE)				
TA-48D-BLK	1" & 1-1/4"	Black	4" to 8"	10	560	\$ 29.87
TA-48D-GREEN	1" & 1-1/4"	Green	4" to 8"	10	560	\$ 31.06
Three Piece The	ermo Plastic Elastor	mer (TPE)				
TA20-68D-BLK	2"	Black	6" to 8"	6		\$ 69.89



## **SPIDER TORQUE ARRESTORS**

Color

Boshart's spider torque arrestors are easily secured to drop pipes with clamps (not included). They feature a unique wire guard feature and the casing size is clearly marked for ease of cutting to size. The suggested clamp for all sizes is 2-SSC8740.

**Drop Pipe Size** 



Quantity List

Primary Material: SBR

Part No.

Part No.



	- 1 - 6 - 16			~	,
				L1 L	2 Price - A
			List	Price Effective:	June 24, 2019
TAS46-10	1"	Black	4" to 6"	60	\$ 10.97
TAS46-12	1-1/4"	Black	4" to 6"	60	\$ 10.44
TAS46-15	1-1/2"	Black	4" to 6"	60	\$ 9.92
TAS46-20	2"	Black	4" to 6"	60	\$ 9.39

**Well Casing Size** 

Color

### **CABLE GUARDS**

Boshart's cable guards will keep the power cable from abrading against the well casing. One should be placed at the pump and one every 15' there after. Each cable guard is 6" in size and has tabs that can be cut to fit 5" or 4" well casing.



Quantity List



Primary Material: Polyethylene

<u> </u>	
7	100
U	_ 10

				L1 L2	Price - A
			List Price	e Effective: Decem	ber 04, 2015
WG-100	Self Clamping	1"	Clear	48	\$ 3.10
WG-6	Snap In	1" & 1-1/4"	Clear	100	\$ 1.29
WG-125	Self Clamping	1-1/4"	Clear	48	\$ 9.32

**Drop Pipe Size** 

## **DROP PIPE COUPLINGS**

Boshart's drop pipe couplings are use to connect drop pipes together in well applications.

Design



Part No. Size Length Quantity List L1 L2 Price - A

List Price Effective: October 15, 2021



### 304 Stainless Steel,

• NSF/ANSI Standard 372 Certified

These couplings have an inside chamfer on both ends for trouble free starting of threads. They have a separate taper to ensure a proper watertight seal and flats on the sides for ease of use with a wrench.

Note: All tensile testing results consistently conclude in joint failure due to the elongation of the male threads on the drop/riser pipe. It is therefor recommended that the installer acquire the male pipe thread load capacity data of the drop/riser pipe from the pipe manufacturer. The loads must not exceed either the coupling or drop/riser pipe load capacity. The maximum load bearing weight of the pipe will vary significantly depending on the pipe material. This data is only a guide. The final responsibility for the design of the well lies with the well designer/installer.

28-SSDPC-10	1"	2-1/2"	10	50	\$ 17.75
28-SSDPC-12	1-1/4"	2-1/2"	10	50	\$ 20.81
28-SSDPC-15	1-1/2"	2-1/2"	10	50	\$ 26.29
28-SSDPC-20	2"	2-1/2"	5	25	\$ 31.03



#### **PVC**

These couplings have a wall thickness that is 30% heavier than Schedule 120 to ensure increased strength and reliability. To be used in well depths no greater than 400'.

28-PDPC-10	1"	2-3/4"	10	100	\$ 8.85
28-PDPC-12	1-1/4"	2-3/4"	10	100	\$ 9.91
28-PDPC-15	1-1/2"	2-3/4"	10	100	\$ 10.00
28-PDPC-20	2"	3"	10	100	\$ 13.52



### **ROPE**

Boshart's rope is available in different lengths and colors.



Part No. Color Length Diameter Reel Tensile **Ouantity List** L2 Price - A Material Strength Lbs L1





#### **Braided Nylon,**

This rope has high elasticity and working strength. It can be stored wet without damage and works well in pulleys, winches, general tie downs, tarps securing and marine use. Solid braid stays round, has a uniform diameter and will not

SRNB-1/4	White	1,000'	1/4"	Plastic	1,200	\$ 215.69
SRNB-3/8	White	1,000'	3/8"	Plywood	2,700	\$ 525.67



#### **Braided Polypropylene**,

This rope is made of 100% monofilament fibers in a hollow braid. It floats on water, retains its strength when wet and may be stored wet without damage. There is a high resistance to abrasion, mildew, oil, grease, gasoline, marine growth and other chemicals. It is best for tie-downs, utility hand lines, pulling lines, ladder lines, and marine uses.

SRPB-1/4-500	Blue & White	500'	1/4"	Plastic	975	\$ 46.88
SRPB-1/4	Blue & White	1,000'	1/4"	Plastic	975	\$ 83.10
SRPB-1/4-3000	Blue & White	3,000'	1/4"	Plywood	975	\$ 235.62




#### Twisted Polypropylene,

This rope is waterproof, floats and easy to handle. It is resists most chemicals, oil, gasoline and is resistant to color fading, abrasion and rot.

SRPT-04-1200BLK	Black	1,200'	1/4"	Plastic	1,120	\$ 140.72
SRPT-04-600B	Blue & White	600'	1/4"	Plywood	1,120	\$ 67.71
SRPT-06-300B	Blue & White	300'	3/8"	Plywood	1,450	\$ 187.21
SRPT-06-600B	Blue & White	600'	3/8"	Plywood	1,450	\$ 154.14
SRPT-08-300B	Blue & White	300'	1/2"	Plywood	3,780	\$ 155.70
SRPT-08-600B	Blue & White	600'	1/2"	Plywood	3,780	\$ 262.10
SRPT-12-300B	Blue & White	300'	3/4"	Plywood	7,650	\$ 329.50
SRPT-1/4	Yellow	1,300'	1/4"	Plastic	1,130	\$ 135.17
SRPT-3/8	Yellow	630'	3/8"	Plastic	2,440	\$ 177.29
SRPT-5/16	Yellow	975'	5/16"	Plastic	1,710	\$ 159.76
SRPT-1/2	Yellow	335'	1/2"	Plastic	3,780	\$ 158.13

### **ROPE HANGER**

Boshart's rope hangers provide an easy method of attaching the safety rope securely to the well casing. The installation of the well cap onto the well casing is unobstructed. They are installed at the top of the well casing and can be easily removed when the pump is serviced or replaced.



Accepts rope sizes: 1/4" to 3/8"

Part No. Well Casing I.D. Quantity List L1 L2 Price - A

List Price Effective: April 27, 2020 \$ 38.15 5 40



STRH-6 6" or 6-1/4"

Contact your sales rep for any further information Toll Free: 1-800-561-3164

boshart.com



# **MECHANICAL SHAFT SEALS**

Boshart's mechanical shaft seals are designed to provide a water tight seal between the pump housing and the motor shaft which drives the impeller.

Part No.	Seat Thickness	Shaft Size	Quantity List
			L1 L2 Price - A





			List Price Effective: September 25, 2017
SS-1000	0.344	0.625	\$ 4.97
SS-2000	0.406	0.625	\$ 4.78
SS-2010	0.406	0.750	\$ 6.02

# **CIRCULATOR COUPLING**

Boshart's circulator couplings are easy to install and quiet when running. They have a long life and superior alignment capabilities. They are easier on the pump and motor, less rigidity puts less load on the bearings and seals.

H.P. rating 1/12 to 1/3

Part No.	Size	Quantity List
		L1 L2 Price - A
		List Price Effective: July 13, 2009
24-15	1/2"	25 200 \$ 11.88



## **NUT DRIVER**

Boshart's nut driver has a flexible shaft and reversible socket.

Part No.	Size	Quantity List
		L1 L2 Price - A
		List Price Effective: April 27, 2020
28-FND	1/4" or 5/16"	100 \$ 10.95





## **PIPE CUTTERS**

Boshart's pipe cutters cut through POLY, PVC, PEX, ABS and CPVC pipe and conduit. They feature a latch for carrying in the closed position. All pipe cutters have a removable and replaceable stainless steel blade.

	Part No.	Cuts Pipe Size	Material	Replacement Blade	Quar L1	ntity L2	List Price - A
				List Price	Effect	tive: A	pril 27, 2020
	28-PC-0110	Up to 1"	Metal,	28-PCRB-0110	12	72	\$ 16.51
	28-PC-0112	Up to 1-1/4"	Metal,	28-PCRBA-0112	6	24	\$ 42.69
	28-PC-0120	Up to 2"	Metal,	28-PCRBA-0120	6	24	\$ 136.63
°	28-PCP-0110	Up to 1"	Nylon,	28-PCPRB-0110	10	60	\$ 13.22

# PIPE CUTTER REPLACEMENT BLADES

These are replacement blades for pipe cutters.

Quantity List Part No. L1 L2 Price - A

List Price Effective: April 27, 2020



		List i fiet Effective. April 27, 2020
28-PCRB-0110	For 28-PC-0110	\$ 9.10
28-PCRBA-0112	For 28-PC-0112	\$ 16.37
28-PCRBA-0120	For 28-PC-0120	\$ 22.51
28-PCPRB-0110	For 28-PCP-0110	\$ 9.10

## **CONTRACTOR BIN**

Boshart's contractor bins are a great plastic storage tote with removable bins. They feature a clear lid with latches to secure contents.

Part No.

**Quantity List** L1 L2 Price - A

 $\mathsf{C}\mathsf{A}$ 



		LIST Price Effective:	April 27, 20	020
28-CBD-09	The bins in this contractor bin are deep, included are: • 3 bins are 6" x 4" x 3-1/2" • 6 bins are 4" x 3" x 3-1/2"	1 1	10 \$ 44	4.81
28-CBD-12	The bins in this contractor bin are deep, included are: • 12 bins are 4" x 3" x 3-1/2"	1	0 \$45	5.70
28-CBS-30	The bins in this contractor bin are shallow, included are: • 18 bins are 3" x 2" x 1-3/4" • 12 bins are 2" x 1-1/2" x 1-3/4"	1	16 \$ 31	1.72



# **TAPE MEASURES**

These tape measures have a heavy duty construction and are rubber encapsulated for durability. They have a locking feature and are imperial as well as metric. Personalization is available on orders of 2000 for the 25' and 3000 for the 6'.

Part No. Quantity List L1 L2 Price - A

List Price Effective: April 27, 2020



		List Price Effective. April 27, 202	.U
28-TM06	Swivel Keychain - 6' (2 meters)	10 200 \$ 2.2	25
28-TM25	Belt clip - 25' (7.5 meters)	10 50 \$13.0	8(