


14-(G)PPE SERIES PLEATED POLYESTER SEDIMENT CARTRIDGE

APPLICATION:

- Pleated surface area provides greater sediment and dirt holding capacity while maintaining flow rate and reducing initial pressure drop
- Suitable for residential, commercial and industrial applications
- Cartridges can be cleaned and reused in most applications

SPECIFICATION:

- Max Temperature Rating: 140°F (60°C)
- Filter media: Polyester
- Filter core: Polypropylene
- Outer Netting: Polypropylene
- End Cap: Polypropylene with TPR Gasket



DIMENSIONS										
Part No.	Inner Diameter		Outer Diameter		Length		Micron Rating	Flow Rate		Weight grams
	inches	mm	inches	mm	inches	mm		PSI Drop @ GPM		
STANDARD										
14-PPE1-01	1.00	25.40	2.50	63.50	9.75	247.65	1	1 PSI @ 10 GPM	200	
14-PPE1-05	1.00	25.40	2.50	63.50	9.75	247.65	5	1 PSI @ 10 GPM	200	
14-PPE1-05-2PK	1.00	25.40	2.50	63.50	9.75	247.65	5	1 PSI @ 10 GPM	200	
14-PPE1-10	1.00	25.40	2.50	63.50	9.75	247.65	10	1 PSI @ 10 GPM	200	
14-PPE1-20	1.00	25.40	2.50	63.50	9.75	247.65	20	1 PSI @ 10 GPM	120	
14-PPE1-20-2PK	1.00	25.40	2.50	63.50	9.75	247.65	20	1 PSI @ 10 GPM	120	
14-PPE1-50	1.00	25.40	2.50	63.50	9.75	247.65	50	1 PSI @ 10 GPM	120	
14-PPE2-05	1.00	25.40	2.50	63.50	20.00	508.00	5	1 PSI @ 10 GPM	300	
14-PPE2-20	1.00	25.40	2.50	63.50	20.00	508.00	20	1 PSI @ 10 GPM	300	
GIANT										
14-GPPE1-01	1.00	25.40	4.50	114.30	9.75	247.65	1	1 PSI @ 10 GPM	290	
14-GPPE1-05	1.00	25.40	4.50	114.30	9.75	247.65	5	1 PSI @ 10 GPM	290	
14-GPPE1-20	1.00	25.40	4.50	114.30	9.75	247.65	20	1 PSI @ 10 GPM	290	
14-GPPE1-50	1.00	25.40	4.50	114.30	9.75	247.65	50	1 PSI @ 10 GPM	290	
14-GPPE2-01	1.00	25.40	4.50	114.30	20.00	508.00	1	1 PSI @ 20 GPM	600	
14-GPPE2-05	1.00	25.40	4.50	114.30	20.00	508.00	5	1 PSI @ 20 GPM	600	
14-GPPE2-20	1.00	25.40	4.50	114.30	20.00	508.00	20	1 PSI @ 20 GPM	600	
14-GPPE2-50	1.00	25.40	4.50	114.30	20.00	508.00	50	1 PSI @ 20 GPM	600	

Always Test Water - Do not use this product with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the filtration system.

Change Out - Replacement filter cartridges have a limited service life. Changes in taste, colour and flow of the water (other liquid) being filtered are signals that replacement of the cartridge may be necessary.

BOSHART
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 800-561-3164

boshart.com ♦ blog.boshart.com