

14-(G)GAC SERIES GRANULAR ACTIVATED CARBON TASTE & ODOUR CARTRIDGE

APPLICATION:

- Designed to remove unpleasant tastes and odours as well as sediment
- Canister design ensures maximum carbon contact time for removal of taste and odour
- Low pressure drop and steady flow rates
- Suitable for residential, commercial and industrial applications
- Suitable for reverse osmosis system or point of use water dispensing system
- Integral post filter to remove small carbon fines and other sediment

SPECIFICATION:

- Max Temperature Rating: 140°F (60°C)
- Max Pressure Rating: 120 PSI
- Filter media: Coconut Shell Activated Carbon
- Filter media: 5 Micron Polypropylene post filter to remove fine sediment
- Filter body: Polypropylene
- End Cap: Polypropylene with TPR Gasket



DIMENSIONS						
Part No.	Outer Diameter		Length		Micron	Weight
	inches	mm	inches	mm	Rating	grams
14-GAC1-05	2.75	69.85	9.88	250.83	5	420
14-GAC2-05	2.75	69.85	20.00	508.00	5	935
14-GGAC1-05	4.50	114.30	9.88	250.83	5	1165
14-GGAC2-05	4.50	114.30	20.00	508.00	5	2835

Always Test Water - Do not use this product with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the filtration system.

Change Out - Replacement filter cartridges have a limited service life. Changes in taste, colour and flow of the water (other liquid) being filtered are signals that replacement of the cartridge may be necessary.

BOSHART
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 800-561-3164

boshart.com ♦ **blog.boshart.com**