





INDEX

Product Line	Page
Relief Valves	1
Snifter & Tank Valves	2
Bleeder Orifices	2
Float Valves	3
Float Plug Adapters	3
Float Rods	4
Floats	4
Jet Pump Air Control	5
Non-Repairable Air Volume Controls	6
Repairable Air Volume Controls	6
Well Air Volume Controls	7
Flow Controls	8



RELIEF VALVES

Boshart's relief valves are recommended for all cold water system installations to protect against damage to piping and pressure tanks. Field adjustments are not recommended for these relief valves. Any changes made to the pre-set pressure is entirely at the risk of the person(s) / company who make the adjustment. Relief valves must be installed so that they drain to a floor drain, sump or other safe location with an air break. If an outlet pipe is used then it must be at least the same diameter as the relief valve outlet.



Spring Material: Stainless Steel

Part No.	Size	Inlet Connection	Outlet Connection	Facroty Pre-Set	L1		Price -A
				List Price Ef	fective:	Janua	ry 07, 201
	ndard 372 Certifi	p to 140°F (60°C), Acc ed	curacy: +/- 15%				
RVNB05-075NL	1/2"	MPT	FPT	75 PSI	10	100	\$ 9.43
RVNB07-075NL	3/4" x 1/2"	MPT	FPT	75 PSI	10	100	\$ 10.20
	ature Range: U ndard 372 Certifi	p to 140°F (60°C), Acc ed	curacy: +/- 15%				
RVNB05-100NL	1/2"	MPT	FPT	100 PSI	10	100	\$ 9.43
RVNB07-100NL	3/4" x 1/2"	MPT	FPT	100 PSI	10	100	\$ 10.20
	mperature Ran ndard 372 Certifi	ge: Up to 140°F (60°C ed	;), Accuracy: +/- 15%				
RVHD05NL	1/2"	MPT	FPT	75 PSI	50		\$ 85.81
RVHD07NL	3/4"	MPT	FPT	75 PSI	25		\$ 97.07
RVHD10NL	1" x 3/4"	MPT	FPT	75 PSI	20		\$ 162.10
	mperature Ran ndard 372 Certifi	ge: Up to 140°F (60°C ed), Accuracy: +/- 15%				
		ed MPT	FPT	65 PSI	10		\$ 274.87
• NSF/ANSI Star RVHD12NL RVHD15NL	ndard 372 Certifi 1-1/4" 1-1/2"	ed MPT FPT	· •	65 PSI 65 PSI	10		\$ 822.99
NSF/ANSI Star	ndard 372 Certifi 1-1/4"	ed MPT	FPT		10		
NSF/ANSI Star RVHD12NL RVHD15NL RVHD20NL 304 Stainless S NSF/ANSI Star	ndard 372 Certifi 1-1/4" 1-1/2" 2" Steel, Accuracy: ndard 372 Certifi	ed MPT FPT FPT +/- 15% ed	FPT FPT FPT	65 PSI 65 PSI	10		\$ 822.99 \$ 840.50
• NSF/ANSI Star RVHD12NL RVHD15NL RVHD20NL 304 Stainless S • NSF/ANSI Star SSRVN05-075	ndard 372 Certifi 1-1/4" 1-1/2" 2" Steel, Accuracy: ndard 372 Certifi 1/2"	ed MPT FPT FPT +/- 15% ed MPT	FPT FPT FPT FPT	65 PSI 65 PSI 75 PSI	10	100	\$ 822.99 \$ 840.50 \$ 19.73
• NSF/ANSI Star RVHD12NL RVHD15NL RVHD20NL	ndard 372 Certifi 1-1/4" 1-1/2" 2" Steel, Accuracy: ndard 372 Certifi	ed MPT FPT FPT +/- 15% ed	FPT FPT FPT	65 PSI 65 PSI		100 100	\$ 822.99 \$ 840.50
NSF/ANSI Star RVHD12NL RVHD15NL RVHD20NL 304 Stainless S NSF/ANSI Star SSRVN05-075 SSRVN07-075	ndard 372 Certifi 1-1/4" 1-1/2" 2" Steel, Accuracy: ndard 372 Certifi 1/2"	ed MPT FPT FPT +/- 15% ed MPT MPT +/- 15%	FPT FPT FPT FPT	65 PSI 65 PSI 75 PSI	10		\$ 822.99 \$ 840.50 \$ 19.73
NSF/ANSI Star RVHD12NL RVHD15NL RVHD20NL 304 Stainless S NSF/ANSI Star SSRVN05-075 SSRVN07-075 304 Stainless S NSF/ANSI Star	ndard 372 Certifi 1-1/4" 1-1/2" 2" Steel, Accuracy: ndard 372 Certifi 1/2" 3/4" x 1/2" Steel, Accuracy: ndard 372 Certifi 1/2"	ed MPT FPT FPT +/- 15% ed MPT MPT +/- 15% ed MPT MPT	FPT FPT FPT FPT	65 PSI 65 PSI 75 PSI 75 PSI	10		\$ 822.99 \$ 840.50 \$ 19.73 \$ 21.16
NSF/ANSI Star RVHD12NL RVHD15NL RVHD20NL 304 Stainless S NSF/ANSI Star SSRVN05-075 SSRVN07-075 304 Stainless S NSF/ANSI Star	ndard 372 Certifi 1-1/4" 1-1/2" 2" Steel, Accuracy: ndard 372 Certifi 1/2" 3/4" x 1/2" Steel, Accuracy: ndard 372 Certifi	ed MPT FPT FPT +/- 15% ed MPT MPT +/- 15% ed	FPT FPT FPT FPT FPT	65 PSI 65 PSI 75 PSI 75 PSI	10	100	\$ 822.99 \$ 840.50 \$ 19.73 \$ 21.16
• NSF/ANSI Star RVHD12NL RVHD15NL RVHD20NL 304 Stainless S • NSF/ANSI Star SSRVN05-075 SSRVN07-075 304 Stainless S • NSF/ANSI Star SSRVN05-100	ndard 372 Certifi 1-1/4" 1-1/2" 2" steel, Accuracy: ndard 372 Certifi 1/2" 3/4" x 1/2" steel, Accuracy: ndard 372 Certifi 1/2" 3/4" x 1/2" 3/4" x 1/2"	ed MPT FPT FPT +/- 15% ed MPT MPT +/- 15% ed MPT MPT	FPT FPT FPT FPT FPT FPT	65 PSI 65 PSI 75 PSI 75 PSI	10 10	100	\$ 822.99 \$ 840.50 \$ 19.73 \$ 21.16

boshart.com



SNIFTER & TANK VALVES

These valves allow air into a system to prevent a vacuum.

NSF/ANSI Standard 372 Certified



Part No. Size Design Quantity List L1 L2 Price -A

List Price Effective: March 26, 2018



MPT, Temperature Range: -10°F to 165°F (-23°C to 73.9°C), Opening Pressure: 3 PSI, Pressure Range: 15-150 PSI

SV-0-NCS	1/8"	Springless	10	100	\$ 3.91
SV-0NL	1/8"	Light Spring - Soft Core	10	100	\$ 2.82
SV-0-SC-VC	1/8"	Light Spring	10	100	\$ 3.96
SV-1-NCS	1/4"	Springless	10	100	\$ 4.67
SV-1-SC-VC	1/4"	Light Spring - Soft Core	10	100	\$ 4.72



MPT, Temperature Range: -40°F to 225°F (-40°C to 107°C), Opening Pressure: 60 PSI, Pressure Range: 0-200 PSI

SV-1NL 1/4"	Standard	10 100	\$ 3.39
-------------	----------	--------	---------

SNIFTER VALVE CAPS

These caps are for snifter valves.

Part No. Description Quantity List L2 Price -A



List Price Effective: March 26, 2018 SV-CAP Black flexible plastic cap - has no sealing unit 10 \$ 0.13 SV-CAP-M Chrome plated steel cap with rubber seal & valve core driver feature

BLEEDER ORIFICES

Bleeder orifices allow for water to be easily drained from submersible pump applications.

Quantity List Part No.

List Price Effective: January 07, 2019

L1

48

NO LEAD

Size Quantity List L1 Price - A L2

List Price Effective: January 07, 2019

Brass, MPT

BOB07NL

Part No.

Rapid opening and closing, complete closure preventing loss of pumping volume. 3/4"

Size



L2 Price - A

Rubber, MPT Fast bleed through its large opening.



BOR10 600 \$ 2.31 40



FLOAT VALVES

The most common use of a float valve is to control the filling of livestock water tanks and water tower cooling tanks as well as many other automatic tank filling applications.



Part No.	Inlet Size	Inlet	Oulet	Outlet	Rod	Qua	ntity	List
		Connection	Size	Connection	Connection	L1	L2	Price -A
					List Price Effe	ective.	lanua	ry 07 2019



Brass, Temperature Range: Up to 180°F (82°C), Maximum Pressure: 125 PSI

SMT connection is straight male thread with a gasket and nut

• NSF/ANSI Standard 372 Certified

28-BFV-05NL 1/2" MPT 1/2" MPT 1/4" - 20 SAE 10 100 \$ 28-BFV-07NL 3/4" MPT 3/4" MPT 1/4" - 20 SAE 10 80 \$ 28-BFV-10NL 1" MPT 1" MPT 1/4" - 20 SAE 10 40 \$	
28-BFV-07NL 3/4" MPT 3/4" MPT 1/4" - 20 SAE 10 80 \$ 28-BFV-10NL 1" MPT 1" MPT 1/4" - 20 SAE 10 40 \$	\$ 17.85
28-BFV-10NL 1" MPT 1" MPT 1/4" - 20 SAE 10 40 \$	\$ 17.41
	\$ 20.03
28-BFV-12NL 1-1/4" FPT Faucet 3/8" - 16 SAE 20 \$	\$ 31.24
	\$ 79.84
28-BFV-15NL 1-1/2" FPT Faucet 3/8" - 16 SAE 20 \$	\$ 76.27
28-BFV-20NL 2" FPT Faucet 3/8" - 16 SAE 20 \$	\$ 84.79
28-BHFV-05NL 1/2" or 3/8" SMT or FPT 1/2" MPT 1/4" - 20 SAE 10 100 \$	\$ 21.00
28-BHFV-07NL 3/4" or 1/2" SMT or FPT 3/4" MPT 1/4" - 20 SAE 10 80 \$	\$ 23.85



PVC. Maximum Pressure: 100 PSI

i vc, waxiiiu	iii i i caadi c. 100	1 31						
28-PFV-05	1/2"	MPT	1/2"	MPT	1/4" - 20 SAE	24	192	\$ 8.50
28-PFV-07	3/4"	MPT	3/4"	MPT	1/4" - 20 SAE	12	144	\$ 9.61
28-PFV-10	1"	MPT	1"	MPT	1/4" - 20 SAE	10	80	\$ 16.44
28-PFV-12	1-1/4"	MPT	1-1/4"	MPT	3/8" - 16 SAE	28		\$ 51.37
28-PFV-15	1-1/2"	MPT	1-1/2"	MPT	3/8" - 16 SAE	40		\$ 45.89

FLOAT VALVE PARTS

These are replacement parts for float valves.

Part No. Description Quantity List L1 L2 Price -A

List Price Effective: January 07, 2019



Lever Assembly					
28-BFVP-LA0310	For 3/8" to 1" float valve	100	\$ 10.43		
28-BFVP-LA1220	For 1-1/4" to 2" float valve	50	\$ 10.81		



Plunger Assemb			
28-BFVP-LA1220	For 1-1/4" to 2" float valve	50	\$ 10.81



. 0	,		
28-BFVP-PA0305	For 3/8" to 1/2" float valve	100	\$ 4.41
28-BFVP-PA07	For 3/4" float valve	60	\$ 7.07
28-BFVP-PA10	For 1" float valve	300	\$ 9.25
28-BFVP-PA1220	For 1-1/4" to 2" float valve	20	\$ 17.81



Replacement Seal Kit

28-BFVP-SK0305	For 3/8" to 1/2" float valve	50	\$ 0.45
28-BFVP-SK07	For 3/4" float valve	100	\$ 0.70
28-BFVP-SK10	For 1" float valve	100	\$ 0.52
28-BFVP-SK1220	For 1-1/4" to 2" float valve	100	\$ 0.88

FLOAT PLUG ADAPTERS

These float plug adapters are used to connect two different types of threads together or where the float rod is a different connection than the float valve requires.

Part No. Size Connection Type Description Quantity List

List Price Effective: January 07, 2019

L2 Price -A



Brass,				
28-BFVA-R434-0	1/4" x 3/8"	Female 20 SAE x MPT	Connects 3/8" thru 1" valve to 8" float	\$ 12.53
28-BFVA-R434-11	3/8"	Female 16 SAE x MPT	Connects 1-1/4" thru 2" valve to 8" float	\$ 12.75
28-BFVA-R435-5	3/8" x 1/4"	Female 20 SAE x Male	Connects 1-1/4" thru 2" valve to 6" or	\$ 31.60
		16 SAE	smaller float	

Contact your sales rep for any further information



FLOAT RODS

Float rods are used for connecting the float to the float valve.



Part No.	Size	Thread	Length	Quantity	List
				L1 L2	Price -A





Stainless Steel, Use to connect 3/8" thru 1" float valves with float balls up to and including 6" diameter.

28-BFVRSS-045	1/4"	Male 20 SAE	4-1/2"	500	\$ 2.16
28-BFVRSS-06	1/4"	Male 20 SAE	6"	500	\$ 2.50
28-BFVRSS-08	1/4"	Male 20 SAE	8"	400	\$ 2.74
28-BFVRSS-10	1/4"	Male 20 SAE	10"	300	\$ 3.06
28-BFVRSS-12	1/4"	Male 20 SAE	12"	200	\$ 3.43

Stainless Steel,

Use to connect 3/8" thru 1" float valves with 8" or larger float balls, or 1-1/4" thru 2" float valves with float balls up to and including 6" diameter.

28-BFVRSS3814-12	3/8" x 1/4"	Male 16 SAE x Male 20 SAE	12"	100	\$ 6.59
28-BFVRSS3814-14	3/8" x 1/4"	Male 16 SAE x Male 20 SAE	14"	100	\$ 6.95
28-BFVRSS3814-10	3/8" x 1/4"	Male 16 SAE x Male 20 SAE	10"	100	\$ 9.17
28-BFVRSS3814-16	3/8" x 1/4"	Male 16 SAE x Male 20 SAE	16"	100	\$ 11.67

Stainless Steel,

Use to connect 1-1/4" thru 2" float valves with 8" diameter and larger float balls.

28-BFVRSS38-10	3/8"	Male 16 SAE	10"	100	\$ 5.24
28-BFVRSS38-12	3/8"	Male 16 SAE	12"	100	\$ 6.39
28-BFVRSS38-14	3/8"	Male 16 SAE	14"	100	\$ 6.75
28-BFVRSS38-16	3/8"	Male 16 SAE	16"	100	\$ 7.52

FLOATS

It is not recommended to use less than an 8" diameter float with 1-1/4" to 2" valves. Due to a lack of buoyancy - 6" & smaller floats can be used where inlet pressure is very low.

Part No.	Float	Size	Thread	Bouyancy	Quar	ntity	List
	Diameter			Lb/CU.FT	L1	L2	Price - A
				List Price Effe	ective: J	anua	ry 07, 2019



Copper,

For open tank service only

28-BFVF-C3	3"	1/4"	Female 20 SAE	0.34	\$ 59.96
28-BFVF-C4	4"	1/4"	Female 20 SAE	0.80	\$ 48.11
28-BFVF-C5	5"	1/4"	Female 20 SAE	1.73	\$ 66.71
28-BFVF-C6	6"	1/4"	Female 20 SAE	3.26	\$ 84.09
28-BFVF-C8	8"	3/8"	Female 16 SAE	8.03	\$ 305.61



Polypropylene, Temperature Range: Up to 175°F (79°C),

- NSF/ANSI Standard 372 Certified
- For open tank service only
- Corrosion resistant
- Float rod connection is not factory threaded, the smooth hole is designed for easy self-tapping by threading the metal float rod into the blind hole

28-BFVF-P5	5"	1/4"	Female 20 SAE	1.20	\$ 7.76
28-BFVF-P6	6"	1/4"	Female 20 SAE	3.40	\$ 25.43
28-BFVF-P8	8"	1/4"	Female 20 SAE	8.40	\$ 36.77





FLOATS

Quantity List Part No. Float Size **Thread** Bouyancy L1 L2 Price - A Diameter Lb/CU.FT List Price Effective: January 07, 2019



Polyethylene, Temperature Range: Up to 150°F (66°C),

- Excellent corrosive resistance, good impact & abrasive resistance
- 4.5" to 6": Float rod connection is not factory threaded, the smooth hole is designed for easy self-tapping by threading the metal float rod into the blind hole
- 8" to 10": Floats have a threaded brass insert rod connection
- Not to be used in applications where they are fully submersed

28-BFVF-PL10	10"	3/8"	Female 16 SAE	1 30	\$ 19.47
28-BFVF-PL4.5	5"	1/4"	Female 20 SAE	400	\$ 1.43
28-BFVF-PL5	5"	1/4"	Female 20 SAE	200	\$ 1.92
28-BFVF-PL6	6"	1/4"	Female 20 SAE	100	\$ 3.70
28-BFVF-PL8	8"	3/8"	Female 16 SAE	50	\$ 11.80



304 Stainless Steel,

· Suitable for use in corrosive fluids where high pressure or extreme temperature may exist





NO Pb(),

JET PUMP AIR CONTROL

Boshart's jet pump air controls are for jet systems that cures waterlogged tanks. They have a positive action control which is simple in construction. There is no flexing diaphragm or metal springs. Jet pump air controls will operate on as little as 5" of vacuum and fits all size tanks up to and including 82 gallon (may be easily manifolded for larger size tanks). Primary Material: Plastic



Part No.	Brand	Maximum	Quantity Lis	st
		Tank Size	L1 L2 Pr	rice -A
			CARL ECC AL R. L. A.	

List Price Effective: December 10, 2012



Air Control

NSF/ANSI Standard 372 Certified

Air Control Installation Package

Contains 4' of poly tubing and (2) 1/4" MIP x 1/4" Barb brass adapters.

NSF/ANSI Standard 372 Certified

AVC-PK	Boshart	82 gal	\$ 12.80

Air Control Package

Contains an air control and the installation package.

NSF/ANSI Standard 372 Certified

AVC-PKC	Rochart	lcn 28	¢ 27 12



NON-REPAIRABLE AIR VOLUME CONTROLS

Pump

These non-repairable air volume controls prolong the pump life by reducing cycling frequency.

Tank

NSF/ANSI Standard 372 Certified

Primary Material: Zinc Plated Steel, Maximum Pressure: 100 PSI

Part No.



Ouantity List

Quantity List

				4	,
	Connection	Connection	Tank Size	L1 l	L2 Price -A
			List Price	e Effective: N	March 30, 2020
Boshart					
AVC45	1/4" MPT	1/4" Male Comp Thread	42 gal	20	\$ 10.90
AVC100	3/8" MPT	1/4" Male Comp Thread	120 gal	20	\$ 10.90
Brady					
AV45	1/4" MPT	1/4" Male Comp Thread	70 gal		\$ 48.31
AV45F	1/4" MPT	1/8" FPT	70 gal		\$ 49.73
AV100	3/8" MPT	1/4" Male Comp Thread	120 gal		\$ 55.97
AV100F	3/8" MPT	1/8" FPT	120 gal		\$ 62.13

Maximum



Repairable air volume controls reduce cycling frequency and can be used on jet, centrifugal & rotary pumps. Primary Material: Zinc-die Cast, Maximum Pressure: 100 PSI

Description

Part No.	Tank Connection	Pump Connection	Maximum Tank Size	Quantity List L1 L2 Price -A
			List Pr	ice Effective: March 30, 2020
Brady				
AV30	1/4" FPT	7/16" - 24 THD	42 gal	\$ 63.21
AV42	1/4" FPT	1/4" FPT	70 gal	\$ 95.83
AV80	1/4" FPT	1/4" FPT	120 gal	\$ 82.20
AV120	1/4" FPT	1/4" FPT	220 gal	\$ 115.87

AIR VOLUME CONTROL REPAIR KITS

These are for the repairable air volume controls. Each kit includes a diaphragm, springs, screws, nuts, ball and seal which are needed for a quick and simple repair job.

	F	L1 L2 Price -A
		List Price Effective: January 07, 2019
AV-30-3A	For AV30	\$ 31.21
AV-42-3A	For AV42	\$ 33.85
AV-80-3A	For AV80	\$ 42.74
AV-120-3A	For AV120	\$ 56.77



Part No.



AVC INSTALLATION KIT

A fitting attaches to suction side of pump for air volume control use and to pressure side of pump for pressure switch use or the second fitting attaches to pump side of AV42, AV80 and AV120 air volume controls for air volume control use. For pressure switch installation, it attaches to pressure switch and pressure side of pump.

Part No. Quantity List
L1 L2 Price -A

List Price Effective: January 07, 2019

Pressure

Includes:

- (2) Fitting No. 75-1/8 1/4" Barb x 1/8" MPT Plastic Fitting
- (2) Fitting No. 75-1/4 1/4" Barb x 1/4" MPT 90 Elbow Plastic Fitting
- (1) Fitting No. 78E 1/4" Barb x 7/16" Compression Elbow Plastic Fitting

Brand

(1) 4' of Polyethylene Tubing 1/4" I.D. x 3/8" O.D.

AVC-UK1 \$31.71

Housing

WELL AIR VOLUME CONTROLS

All housings are tapped for use with a 1/4" FPT gauge.

Part No.



Quantity List

				Range	L1 L2	Price -A
				List Price Effec	tive: Septem	ber 25, 2017
• Air release val • NSF/ANSI Stan	ve factory set at	25 PSI				
AVC-AE10	Boshart	Plastic	1-1/4" MPT	0-40 PSI	50	\$ 23.13
Deep Well Adju • Air release val • NSF/ANSI Stan	ve factory set at	25 PSI ed				
AVC-DW-AR	Boshart	Zinc die-cast	1-1/4" MPT	0-40 PSI	50	\$ 26.66
Deep Well Air I NSF/ANSI Stan		ed				
AVC-DWP	Boshart	Plastic	1-1/4" MPT		50	\$ 18.95
• 48" of 1/4" pol • NSF/ANSI Stan	y tubing & bras	s mini barb adapte ed	ers included			
AVC-L	Ametek	Zinc die-cast	1-1/4" MPT		20	\$ 87.70
Deep Well Air I NSF/ANSI Stan		ed				
AVC-PENN-WJ	PENN	Plastic	1-1/4" MPT		50	\$ 37.52
Shallow Well C • 48" of 1/4" pol • NSF/ANSI Stan	y tubing & bras	s mini barb adapto ed	ers included			
AVC-SW	Boshart	Zinc die-cast	1-1/4" MPT		50	\$ 22.81
• Air release val • NSF/ANSI Stan	ve factory set at	25 PSI ed				
AVC-WJ	Ametek	Zinc die-cast	1-1/4" MPT	0-40 PSI	20	\$ 58.54

Tank Connection

boshart.com

Rev. 5.0



FLOMATIC FLOW CONTROLS

These automatic flow control valves are designed to give constant flow over a wide pressure range. The internal controlling mechanism has no moving part, consisting only of a flexible orifice that varies with applied pressure maintaining a constant flow rate.



• NSF/ANSI 61 & 372

Temperature Range: Up to 180°F (82°C)

Part No. Flow Quantity List L1 L2 Price

L1 L2 Price - A List Price Effective: March 30, 2020 Part No. Flow

3/4" MPT x FPT

Quantity List L1 L2 Price - A

List Price Effective: March 30, 2020



Stainless Steel, Hex: 0.875" Overall Length: 1.75"





1/2" FPT

3/4" FPT

Stainless Steel, Hex: 1.000" Overall Length: 2.00"

CDB1.0	1 GPM	\$ 28.92
CDB1.5	1.5 GPM	\$ 28.92
CDB2.0	2 GPM	\$ 28.92
CDB2.5	2.5 GPM	\$ 28.92
CDB3.0	3 GPM	\$ 28.92
CDB3.5	3.5 GPM	\$ 28.92
CDB4.0	4 GPM	\$ 28.92
CDB5.0	5 GPM	\$ 28.92
CDB6.0	6 GPM	\$ 28.92



1" FPT

Stainless Steel, Hex: 1.500" Overall Length: 2.75"

Stainless Steel, Hex: 1.250" Overall Length: 1.50"

1 GPM



\$ 61.16

CDY1.5	1.5 GPM	\$ 61.16
CDY2.0	2 GPM	\$ 61.16
CDY2.5	2.5 GPM	\$ 61.16
CDY3.0	3 GPM	\$ 61.16
CDY4.0	4 GPM	\$ 61.16
CDY5.0	5 GPM	\$ 61.16
CDY6.0	6 GPM	\$ 61.16
CDY7.0	7 GPM	\$ 61.16
CDY8.0	8 GPM	\$ 61.16
CDY9.0	9 GPM	\$ 61.16
CDY10	10 GPM	\$ 61.16
CDY11.5	11.5 GPM	\$ 61.16



Stainless Stee	el, Hex: 1.250" Overall Length: 2.25"	
CDC1.0	1 GPM	\$ 48.21
CDC1.5	1.5 GPM	\$ 48.21
CDC2.0	2 GPM	\$ 48.21
CDC2.5	2.5 GPM	\$ 48.21
CDC3.0	3 GPM	\$ 48.21
CDC3.5	3.5 GPM	\$ 48.21
CDC4.0	4 GPM	\$ 48.21
CDC4.5	4.5 GPM	\$ 48.21
CDC5.0	5 GPM	\$ 48.21
CDC6.0	6 GPM	\$ 48.21
CDC7.0	7 GPM	\$ 48.21
CDC8.0	8 GPM	\$ 48.21
CDC9.0	9 GPM	\$ 48.21
CDC10	10 GPM	\$ 48.21
CDC11.5	11.5 GPM	\$ 48.21

CDX1.0	1 GPM	\$ 56.72
CDX1.5	1.5 GPM	\$ 56.72
CDX2.0	2 GPM	\$ 56.72
CDX2.5	2.5 GPM	\$ 56.72
CDX3.0	3 GPM	\$ 56.72
CDX3.5	3.5 GPM	\$ 56.72
CDX4.0	4 GPM	\$ 56.72
CDX4.5	4.5 GPM	\$ 56.72
CDX5.0	5 GPM	\$ 56.72
CDX5.5	5.5 GPM	\$ 56.72
CDX6.0	6 GPM	\$ 56.72
CDX7.0	7 GPM	\$ 56.72
CDX8.0	8 GPM	\$ 56.72
CDX9.0	9 GPM	\$ 56.72
CDX10	10 GPM	\$ 56.72
CDX12	12 GPM	\$ 56.72
CDX15	15 GPM	\$ 56.72
CDX20	20 GPM	\$ 56.72
CDX25	25 GPM	\$ 56.72
CDX30	30 GPM	\$ 56.72



FLOMATIC FLOW CONTROLS

Part No. Flow Quantity List
L1 L2 Price - A
List Price Effective: March 30, 2020

Part No.

CDT9.0

CDT10

CDT12

CDT15

CDT20

CDT25 CDT30 Flow

9 GPM

10 GPM

12 GPM

15 GPM

20 GPM 25 GPM

30 GPM

Quantity List L1 L2 Price - A

List Price Effective: March 30, 2020



1-1/4" MPT

Stainless Steel, Hex: 1.625" Overall Length: 3.00"

CDP1.0	1 GPM	\$ 102.82
CDP1.5	1.5 GPM	\$ 102.82
CDP2.0	2 GPM	\$ 102.82
CDP2.5	2.5 GPM	\$ 102.82
CDP3.0	3 GPM	\$ 102.82
CDP3.5	3.5 GPM	\$ 102.82
CDP4.0	4 GPM	\$ 102.82
CDP5.0	5 GPM	\$ 102.82
CDP6.0	6 GPM	\$ 102.82
CDP7.0	7 GPM	\$ 102.82
CDP8.0	8 GPM	\$ 102.82
CDP9.0	9 GPM	\$ 102.82
CDP10	10 GPM	\$ 107.08
CDP12	12 GPM	\$ 107.08
CDP15	15 GPM	\$ 107.08
CDP20	20 GPM	\$ 107.08
CDP25	25 GPM	\$ 107.08
CDP30	30 GPM	\$ 107.08





\$ 138.16

\$ 138.16

boshart.com



DOLE FLOW CONTROLS

These automatic flow control valves are designed to give constant flow over a wide pressure range. The internal controlling mechanism has no moving part, consisting only of a flexible orifice that varies with applied pressure maintaining a constant flow rate.

NO LEAD <0.25% Pb by weighted avg.

• NSF/ANSI 372 Certified


Temperature Range: Up to 180°F (82°C),

Part No. Flow Quantity List
L1 L2 Price - A
List Price Effective: July 05, 2019

Part No. Flow Quantity List L1 L2 Price - A

List Price Effective: July 05, 2019

3/8" FPT





1" FPT

Hex: 1.500" Overall Length: 2.75"

FCGX-13.5NL	13.5 GPM	24	\$ 66.73



2" MPT

Zinc Plated Steel, Hex: 2.375" Overall Length: 3.00"

FCGF-10NL	10 GPM	\$ 245.74
FCGF-11.5NL	11.5 GPM	\$ 245.74
FCGF-12NL	12 GPM	\$ 245.74
FCGF-13.5NL	13.5 GPM	\$ 245.74
FCGF-15NL	15 GPM	\$ 245.74
FCGF-20NL	20 GPM	\$ 245.74
FCGF-25NL	25 GPM	\$ 245.74
FCGF-30NL	30 GPM	\$ 245.74



Zinc Plated Steel, Hex: 2.875" Overall Length: 4.00"



FCGH-30NL	30 GPM	\$ 483.25
FCGH-35NL	35 GPM	\$ 483.25
FCGH-40NL	40 GPM	\$ 483.25
FCGH-45NL	45 GPM	\$ 483.25
FCGH-50NL	50 GPM	\$ 483.25
FCGH-55NL	55 GPM	\$ 483.25
FCGH-60NL	60 GPM	\$ 483.25
FCGH-65NL	65 GPM	\$ 483.25
FCGH-70NL	70 GPM	\$ 483.25
FCGH-75NL	75 GPM	\$ 483.25
FCGH-80NL	80 GPM	\$ 483.25
FCGH-85NL	85 GPM	\$ 483.25
FCGH-90NL	90 GPM	\$ 483.25

3" MPT

Zinc Plated Steel, Hex: 3.500" Overall Length: 4.00"



FCGK-30NL	30 GPM	\$ 503.07
FCGK-35NL	35 GPM	\$ 503.07
FCGK-40NL	40 GPM	\$ 503.07
FCGK-45NL	45 GPM	\$ 503.07
FCGK-50NL	50 GPM	\$ 503.07
FCGK-55NL	55 GPM	\$ 503.07
FCGK-60NL	60 GPM	\$ 503.07
FCGK-65NL	65 GPM	\$ 503.07
FCGK-70NL	70 GPM	\$ 503.07
FCGK-75NL	75 GPM	\$ 503.07
FCGK-80NL	80 GPM	\$ 503.07
FCGK-85NL	85 GPM	\$ 503.07
FCGK-90NL	90 GPM	\$ 503.07
FCGK-95NL	95 GPM	\$ 503.07
FCGK-100NL	100 GPM	\$ 503.07
FCGK-105NL	105 GPM	\$ 503.07
FCGK-110NL	110 GPM	\$ 503.07
FCGK-115NL	115 GPM	\$ 503.07
FCGK-120NL	120 GPM	\$ 503.07